PATENT

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

n the Application of: Vogel et al.

CASE NO: AD6728 US NA

APPLICATION NO.: 09/833,452

GROUP ART UNIT: 1773

FILED: 04/12/2001

EXAMINER: Jackson, Monique R

FOR: Multi-Layered, Co-Extruded Ionomeric Decorative Surfacing

RULE 131 DECLARATION

Commissioner for Patents P.O. Box 1450 Alexandria VA 22313-1450

Sir:

I, Lori J. Pike, declare that:

I am a citizen of the United States of America residing in Newark, Dclaware;

I am a co-inventor of the above-identified application for US patent and have read the Office Action mailed 01/10/2007;

I have been employed by E. I. du Pont de Nemours & Company (DuPont) since June - 1981 as an engineer working in various areas of plant support, process engineering, and technical service and development of ethylene copolymers including polymers for film and sheet since 1985;

I made several runs of coextruded two layer films comprising ionomer Surlyn[®] film as top layer and another ionomer Surlyn[®] film as second layer well before December 15, 1998;

I had reduced my invention, before December 15, 1998, as described and claimed in the subject application in this country, evidenced by the following exhibits:

Exhibit A, attached hereto, is a photocopy of work request 710802 by me (L. Pike) and operated by Bruce Dennison and Earl Herriman as operators; two runs are shown on this Exhibit A (Sample number E203-56-51 and E203-56-2); the equipment employed was a coextruder located at DuPont's Chestnut Run facility in Wilmington, Delaware; the resins shown on the farthest left column of the request represents were Surlyn® 1706 (zinc ionomer) and Surlyn® 7930 (lithium ionomer), both were manufactured and sold by DuPont at that time; Exhibit A also shows that an additive CONPOL 5B10S1 was present in one of the

Application/Control Number: 09/833_452

Page 2

ionomer layers; CONPOL was used as antiblock and slip agent additive with different concentrations (0.05 wt % and 0.01 wt %) in the two runs:

Several other two layer films were also made similarly; for example, Exhibit B (work request 150405) shows four (4) two-layer runs (sample numbers E229-41-1, E229-41-2, E229-41-3, E229-41-4); each of runs E229-41-1 and E229-41-2 comprised Surlyn® 1601 film as top layer and another Surlyn® NWL film as second layer; each of run E229-41-3 and E229-41-4 comprised Surlyn® HT 2010 film as top layer and another Surlyn® NWL film as second layer; Surlyn® 1601 and Surlyn® NWL were each a sodium ionomer; Surlyn® HT 2010 was a high transparency sodium ionomer grade.

Not shown are more ionomer/ionomer two-layer runs carried out by me, but the above-illustrated two exhibits unequivocally demonstrate that I conceived and reduced to practice the invention claimed in the above-identified application before the filing date of the parent application of the Smith reference relied on by the examiner; and

I further declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issuing thereon.

Lori J. Pike / Date

upplication No. 09/833,452

ocket No. AD6728 US NA

FILE

BLOWN

;

RECORD

DATA

EXTRUSION



BEST AVAILABLE COPY

EXHIBIT A

α 48 29 ᄎ유 유 2,00 Chilled OUTPUT Adaptor Air Temp PPH PSI + Amt 2730FT 7808C どろうして ઉ 9661 1980 76 77 h 4 9-292-27 SPEED SCREW 2 2 G COUCESTER 9 S WOOP SLATS ADCOUSE 1435-1435-1435-1446 21/ 12/2" MELT Temp. "F HEIGHT ANGLE TOWER SCREW DIE 442 446 子子 435 TOP DIE TEMP. ºF (SET/READ) 435 Botton CENTER DAVIS 1432 30 7327 755 435 NECK 435 435 737 BARREL TEMP. ºF (SET/READ)

CENTER | CENTER | RONT | HEAD | Adaptor イスケーススケ **WELEX** 7337 133 435 435435 435 4357435 435/435 400 425 435 EXTRUDER DATE 435 分 75 3 15/ 375 375 PIKE REAR 3320 333 E 203-56-1 208017 Ĺ E203-56-1 SAMPLE NUMBER ERRIMAN) DENNISON HERRIMAN 30317879 30717955 30360013 LOT NUMBER DATA OPERATOR/ENGINEER WORK REQUEST NO. 56/05/2 50/05/2 0.05/25/P なられる 7930 1706 54KUN 1930 150185 Sualyw. to the state RESIN

BEST AVAILABLE COPY

EXHIBIT B

BLOWN : RECORD DATA EXTRUSION

	TO THE	53.7.1.25		<u>1</u>		1-1-1			
	Adaptor Air Temp. PSI + Amt. 1		1 1 24	2				++++	+
	\ 	38.50	0.6%	3150		-		++++	-
4	24 7 7 7 8 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	776 6	23	<u> </u>			_	++++	_
1. J	SCREW SPAND SC SC SCED SPAND SC SCREW	3 3 3	30	:8					-
4-297-27						_			-
	TOWER TOWER								
SCREW	MELT TOWER TOWER TOWER TOWER TOWER TOWER TOWER TOWER TOWER	25 5		ر خ ک					
			9	3					
	SET/READ) CENTER TOP GUC YUC	 	9	760					
		3	3	7 600					
	DIE TEMP. " DIE TEMP. " NECK Bottom 4UJO 1UC	7 (20)	23.	7 205					
	Z J	7 CD7 7	7,007	55					
	Welex ND Adaptor O 400 CO 400			2 2					
	1 LGC C C C C C C C C C C C C C C C C C C	2 3 7			-		-		
	REL TEMP. *F (SET/READ) REL TEMP. *F (SET/READ) RENTER FRONT	5 g	5 5 5 5	3					+
DATE	EXTRUDER FEMP. *F (SET) CENTER NTER FRONT NTER FRONT NTER FRONT NTER NTER NTER NTER NTER NTER NTER NT	<u> </u>	7	$- \mathcal{F} $		+			
A A	BARREL TEMP. F BARREL TEMP. F SINTER CENTER FRO SINTER STO HO SINTER STORY SINTER ST	390	350	390				++++	+-
	BARI BEATE 375	37,5	37,518	333				++++	
	350 350	350	350	350	1-1-1			++++	-
	PIKE 3	1 3	4-1	7	41.5				
1,0	SAMPLE NUMBER C339-41-	6-14-8663	E 239 - 41	E 229-41-4	E-229-41-5				
30405	C C C C C C C C C C C C C C C C C C C		-						
	NEER DATA LOT NUMBER	2 2	4. 40 de	V. elek					
THORK REOUEST NO.	OPERATOR/ENGINEER DENNISCH RESIN DATA SAM TYPE NUMBER NUM SARAN (LO) (JURIEY EARS-			· 1			+-		++
REOU	OPERATOR/E RESIN TYPE SURLUAN (GO)	2,82,70 160 i	SUPLIVA HIZEID	Survay HT20i0	7 7				
A dOW	OPER Syky	SVRLYN NWL SVRLYN 160 i	23.2	MT20iO	Sugard				1